

MJP 11.5

This vertical mast platform is battery-powered. It has a light but robust structure to work in total safety. The 345° turret rotation is the optimal solution to work both indoor and outdoor. The boom tilt is very useful for indoor maintenance.



STANDARD EQUIPMENTS:

- Proportional controls
- Pothole protection
- Self-locking door on the platform
- Permissible side-shift at maximum height
- platform horizontal outreach
- Non-marking tyres
- 2WD
- Automatic braking system
- Emergency lowering
- Emergency stop button
- Cylinder locking valve
- Onboard diagnostics system
- Tilt indicator with alarm
- Movement alarm sensor
- Horn
- Counter Hour
- Charger protection
- Flashing beacon
- Swing-out carter for easy maintenance
- 345° turret rotation
- 3 m horizontal extension

MJP 11.5	
Load capacity	200 kg
Max no. occupants	2
Working height	11.2 m
Max platform height	9.2 m
Max horizontal outreach	3 m
Up and over height	7.89 m
A Overall length	2.72 m
B Overall width	1 m
H Overall height	1.99 m
Platform size (length/width)	0.62 m x 0.87 m
Ground clearance (stowed)	0.06 m
Ground clearance (raised)	0.019 m
C Wheelbase	1.22 m
Turning radius (inside/outside)	0.23 / 1.65 m
Turret rotation	345°
Jib movement	+70°/-60°
Drive motor	24 V / 1.5 kW
Lifting motor	24 V / 3 kW
Travel speed (stowed)	4.5 km/h
Travel speed (rated)	0.5 km/h
Up/Down Speed	95 / 50 sec
Batteries	24 V / 240 Ah
Integrated charger	24 V / 30 A
Gradeability	25%
Maximum working slope (indoor use)	2.5°
Tyres	381x127 mm
Weight	2,950 kg



Pothole protection



Zero turning radius

STANDARDS COMPLIANCE:
EN 280, ANSI/SAIA A92.20

