Compact and solid Push Saw for small services and repair jobs in roadworks. The height adjustable Anti-Vibration Handles have a clear focus on operators convenience.







Motorstop



Cutting depth indicator



Lifting frame



Attachable water tank, easy to fill

Machine with

Machine with KOHLER Engine



Parking break



Adjustable anti vibration handles for operators comfort



Cutting depth locking device



Cutting depth adjustment by handwheel

13 HP Honda gas engine Blade-ø 450mm (18") Cutting depth 165 mm (6,5")

- Adjustable anti vibration handles for operators comfort
- Cutting depth adjustment by handwheel
- Cutting depth indicator
- Front cutting guide
- Parking break
- Lifting frame
- 25 Liter water tank, easy to fill
- Big rear wheels for good chassis clearance
- Durable Poly-V belt for an optimum of power transmission

Specifications	GÖLZ FS 175	GÖLZ FS 175 KOHLER	
Max Cutting depth	165 mm		
Blade diameter	450 mm		
Shaft size	25,4 mm		
Water tank	25 Liter (6,6 gal)		
Engine	Honda GX390	KOHLER Engine CH440	
Engine power (net power)	13 HP / 9,5 kW (11,8 HP / 8,7 kW)	14 HP / 10,5 kW (12,7 HP / 9,4 kW)	
Shaft speed	2.300 min ⁻¹		
Feed motion	Push		
Cutting depth adjustment	Handwheel		
Power transmission	Poly-V Belt		
Hand Arm Vibrations	4,5 m/s ²	2,2 m/s ²	
Dimensions (LxWxH)	1.220 x 491 x 1.160 mm	1.210 x 630 x 1.165 mm	
Weight	110 kg (242 lbs)	112 kg (246 lbs)	
Order number	0282 175 6000	0282 175 6020	

Accessories

Diamond Blades for Asphalt and Concrete, please check our Diamond Tools catalog.

Robust and solid Push Saw with hot galvanized chassis for durable operation in the construction and rental business with ergonomical comfort to the operator by Anti-Vibration-System and height adjustable handles.





Attachable water tank 25 l, easy to fill



Cutting depth adjustment by foot pedal



Cutting depth indicator



Big rear wheels for easy moving on the construction site



Parking break



Machine with KOHLER Engine

Gasoline, Diesel or Electric motor Blade-ø 500mm (20") Cutting depth 190 mm (7,5")

- Anti-Vibration system, height adjustable handles
- Cutting depth adjustment by foot pedal for operators safety
- Cutting depth indicator
- Front cutting guide
- Parking break
- Safety frame with integrated lifting frame
- 25 Liter water tank, easy to fill
- Big wheels for good chassis clearance
- Durable V-belt drive
- Maintenance free design (hot dipped galvanized chassis)

Available with Honda 13HP, KOHLER 14HP, Yanmar 10HP diesel engine or 400V, 5,5 KW 3-phase electric motor (p. 89).

Specifications	GÖLZ FS 170	GÖLZ FS 170 KOHLER	GÖLZ FS170 YANMAR
Max Cutting depth	190 mm		
Blade diameter	500 mm		
Shaft size	25,4 mm		
Water tank	25 Liter (6,6 gal)		
Engine	Honda GX390	KOHLER Motor CH440	Yanmar LA100 (Diesel)
Engine power (net power)	13 HP / 9,5 kW (11,8 HP / 8,7 kW)	14 HP / 10,5 kW (12,7 HP / 9,4 kW)	10 HP / 7,4 kW
Shaft speed	2.300 min ⁻¹		
Feed motion	Push		
Cutting depth adjustment	Footpedal & Pneumatic Spring		
Power transmission	V-Belt Kit		
Hand Arm Vibrations	4,5 m/s ²		
Dimensions (LxWxH)	1.210 × 630 × 1.165 mm		
Weight	120 kg (264 lbs)	122 kg (268 lbs)	130 kg (286 lbs)
Order number	0282 170 1000	0282 170 1400	0282 170 1100



height adjustable handles

Accessories

Diamond Blades for Asphalt and Concrete, please check our Diamond Tools catalog.